



## DATA SHEET

Version	0
Date	01/01/22
Page	1 of 1

### MASTIK EXTRA

### Natural rubber based solvent adhesive

#### CHARACTERISTICS

Natural rubber based solvent adhesive	METHOD	QUALITY CHARACTERISTICS (U.M.)
Appearance and Color	Visual	Clear opalescent
Viscosity	IO 07/42.10	4.500 – 5.000 cps
Time Open	IO 07/42.6	At room temperature around 2 hours
Specific weight	IO 07/42.3	0,650 – 0,700 g/cc
Dry content	IO 07/42.4	11 – 13%

#### USES

**Mastik Extra** is a natural rubber-based adhesive particularly suitable for seaming; thanks to the rapid drying, good tackiness and non-aggressiveness towards the finishes of both synthetic and natural materials. It is indicated in the construction of uppers and in small leather goods.

#### INSTRUCTIONS FOR USE

Apply by brush or spreading machine on one or both surfaces to be glued, couple immediately and exert a slight pressure.

#### STORAGE

The product should be stored in the original packaging at room temperature (5-35°C). In these conditions it remains suitable for about 12 months.

Particularly low storage temperatures lead to a considerable reversible thickening of the product and, consequently, a more difficult distribution. Shake well before use.

#### PACKAGING

Contentori metallici Kg. netti 4 – 13 – 40

#### NOTES

**Mastik Extra** is highly flammable: make sure that the systems used for handling are properly grounded to avoid the accumulation of electrostatic charges.